

CLEAN BALANCER SURFACE of all foreign material.

INSTALL SLEEVE: Apply a thin coat of locking compound to the neck of the balancer. Using a flat block, tap sleeve gently over the shaft until it bottoms.

REMOVE ALL SEALER from outer surface of sleeve.

LUBRICATE OUTER SURFACE of sleeve and lip by applying a thin coat of grease or motor oil.

TO COMPLETE INSTALLATION, use standard pulley installation procedures and standard seal.

© 2001 Federal-Mogul Corp.
Form No. I-663 (Rev. 5/01)

Printed in U.S.A.

CLEAN BALANCER SURFACE of all foreign material.

INSTALL SLEEVE: Apply a thin coat of locking compound to the neck of the balancer. Using a flat block, tap sleeve gently over the shaft until it bottoms.

REMOVE ALL SEALER from outer surface of sleeve.

LUBRICATE OUTER SURFACE of sleeve and lip by applying a thin coat of grease or motor oil.

TO COMPLETE INSTALLATION, use standard pulley installation procedures and standard seal.

© 2001 Federal-Mogul Corp.
Form No. I-663 (Rev. 5/01)

Printed in U.S.A.

CLEAN BALANCER SURFACE of all foreign material.

INSTALL SLEEVE: Apply a thin coat of locking compound to the neck of the balancer. Using a flat block, tap sleeve gently over the shaft until it bottoms.

REMOVE ALL SEALER from outer surface of sleeve.

LUBRICATE OUTER SURFACE of sleeve and lip by applying a thin coat of grease or motor oil.

TO COMPLETE INSTALLATION, use standard pulley installation procedures and standard seal.

© 2001 Federal-Mogul Corp.
Form No. I-663 (Rev. 5/01)

Printed in U.S.A.

CLEAN BALANCER SURFACE of all foreign material.

INSTALL SLEEVE: Apply a thin coat of locking compound to the neck of the balancer. Using a flat block, tap sleeve gently over the shaft until it bottoms.

REMOVE ALL SEALER from outer surface of sleeve.


LUBRICATE OUTER SURFACE of sleeve and lip by applying a thin coat of grease or motor oil.

TO COMPLETE INSTALLATION, use standard pulley installation procedures and standard seal.

© 2001 Federal-Mogul Corp.
Form No. I-663 (Rev. 5/01)

Printed in U.S.A.

To insure proper function of this product on this application this sleeve must be aligned perfectly, straight and true and fully bottomed on the balancer hub before assembly.




GLEEVE 'N' SEAL®

FEL-PRO INSTALLATION TIPS



To insure proper function of this product on this application this sleeve must be aligned perfectly, straight and true and fully bottomed on the balancer hub before assembly.




GLEEVE 'N' SEAL®

FEL-PRO INSTALLATION TIPS



To insure proper function of this product on this application this sleeve must be aligned perfectly, straight and true and fully bottomed on the balancer hub before assembly.




GLEEVE 'N' SEAL®

FEL-PRO INSTALLATION TIPS



To insure proper function of this product on this application this sleeve must be aligned perfectly, straight and true and fully bottomed on the balancer hub before assembly.



GLEEVE 'N' SEAL®

FEL-PRO INSTALLATION TIPS



CLEAN BALANCER SURFACE of all foreign material.

INSTALL SLEEVE: Apply a thin coat of locking compound to the neck of the balancer. Using a flat block, tap sleeve gently over the shaft until it bottoms.

REMOVE ALL SEALER from outer surface of sleeve.

LUBRICATE OUTER SURFACE of sleeve and lip by applying a thin coat of grease or motor oil.

TO COMPLETE INSTALLATION, use standard pulley installation procedures and standard seal.

© 2001 Federal-Mogul Corp.
Form No. I-663 (Rev. 5/01)

Printed in U.S.A.

CLEAN BALANCER SURFACE of all foreign material.

INSTALL SLEEVE: Apply a thin coat of locking compound to the neck of the balancer. Using a flat block, tap sleeve gently over the shaft until it bottoms.

REMOVE ALL SEALER from outer surface of sleeve.

LUBRICATE OUTER SURFACE of sleeve and lip by applying a thin coat of grease or motor oil.

TO COMPLETE INSTALLATION, use standard pulley installation procedures and standard seal.

© 2001 Federal-Mogul Corp.
Form No. I-663 (Rev. 5/01)

Printed in U.S.A.

CLEAN BALANCER SURFACE of all foreign material.

INSTALL SLEEVE: Apply a thin coat of locking compound to the neck of the balancer. Using a flat block, tap sleeve gently over the shaft until it bottoms.

REMOVE ALL SEALER from outer surface of sleeve.

LUBRICATE OUTER SURFACE of sleeve and lip by applying a thin coat of grease or motor oil.

TO COMPLETE INSTALLATION, use standard pulley installation procedures and standard seal.

© 2001 Federal-Mogul Corp.
Form No. I-663 (Rev. 5/01)

Printed in U.S.A.

CLEAN BALANCER SURFACE of all foreign material.

INSTALL SLEEVE: Apply a thin coat of locking compound to the neck of the balancer. Using a flat block, tap sleeve gently over the shaft until it bottoms.

REMOVE ALL SEALER from outer surface of sleeve.


LUBRICATE OUTER SURFACE of sleeve and lip by applying a thin coat of grease or motor oil.

TO COMPLETE INSTALLATION, use standard pulley installation procedures and standard seal.

© 2001 Federal-Mogul Corp.
Form No. I-663 (Rev. 5/01)


Printed in U.S.A.

To insure proper function of this product on this application this sleeve must be aligned perfectly, straight and true and fully bottomed on the balancer hub before assembly.




FEL-PRO INSTALLATION TIPS
FEL-PRO
GLEEVE 'N' SEAL®

To insure proper function of this product on this application this sleeve must be aligned perfectly, straight and true and fully bottomed on the balancer hub before assembly.




FEL-PRO INSTALLATION TIPS
FEL-PRO
GLEEVE 'N' SEAL®

To insure proper function of this product on this application this sleeve must be aligned perfectly, straight and true and fully bottomed on the balancer hub before assembly.



FEL-PRO INSTALLATION TIPS
FEL-PRO
GLEEVE 'N' SEAL®

To insure proper function of this product on this application this sleeve must be aligned perfectly, straight and true and fully bottomed on the balancer hub before assembly.



FEL-PRO INSTALLATION TIPS
FEL-PRO
GLEEVE 'N' SEAL®