

2

BLACK INK
ON WHITE PAPER

4.250

INSTALLATION INSTRUCTIONS FOR
MERCEDES-BENZ 200D AND 220D

1. REMOVE SHELL FROM ENGINE MOUNTING BASE.
2. CAREFULLY REMOVE NYLON DISC FROM SHELL AND CLEAN IN SUITABLE SOLVENT.
3. REMOVE AND DISCARD REPLACEABLE FILTER ELEMENT FROM SHELL.
4. AFTER CLEANING SHELL, INSTALL NEW FILTER ELEMENT OVER CENTER BOLT WITH REMOVAL HANDLE POINTING TOWARD OPEN END.
5. PLACE NYLON DISC (MERCEDES BENZ PART # 001845725) OVER CENTER BOLT UNTIL IT CONTACTS FILTER ELEMENT.
6. TO AVOID POSSIBLE LEAKAGE PROBLEMS, ALWAYS REPLACE THE HOUSING SEALING GASKET. THIS IS AN O-RING STYLE GASKET AND IS A SPECIAL ORDER ITEM AVAILABLE FROM THIS MANUFACTURER. PLEASE REFER TO THE TECHNICAL DATA SECTION OF THE APPROPRIATE MASTER CATALOG FOR THE CORRECT PART # TO BE ORDERED. DO NOT USE THE GASKET SUPPLIED WITH THIS FILTER FOR MERCEDES BENZ APPLICATIONS.
7. AFTER FILTER IS REASSEMBLED, FILL CRANKCASE, START ENGINE AND CHECK FOR LEAKS.

5.500

PRINTED IN U.S.A.

14-42222